



FUNCTION TABLE:

COM127	COM128
COM1	COM2
SEG70	SEG309

30	D15
29	D13
28	D8
27	D7
26	D6
25	D5
24	D4
23	D3
22	D2
21	D1
20	D0
19	RST
18	WR
17	RD
16	A0
15	CS0
14	BM0
13	BM1
12	TEST4
11	YSS
10	VDD
9	VDD23
8	VB0+
7	VB1+
6	VB1-
5	VB0-
4	VS-
3	VS+
2	VLCDIN
1	VLCDOUT
NO.	SYMBOL

- NOTES:
1. DISPLAY TYPE: STN-BLUE
  2. VIEWING DIRECTION : 6 O'CLOCK
  3. POLARIZER: TRANSMISSIVE/NEGATIVE
  4. DRIVE METHOD: 1/128 DUTY 1/12BIAS
  5. OPERATING VOLTAGE: 16.0V
  6. OPERATING TEMP: -20°C ~ 70°C
  7. STORAGE TEMP : -30°C ~ 80°C
  8. CONNECTOR: COG (IC:UC1698U)
  9. GENERAL TOLERANCE: ±0.2

REVISION RECORD	DATE	TITLE	FILE NAME	Rev.	P/N
1		LCD OUTLINE DIMENSION	WM1240128K4	0	
2					
3					
4					
5					
6					

  

FILE NO. : LCD-	Ver. : A	SCALE :
DRAWN BY : 杨晓雷	DATE : 20131021	UNIT : mm
CHECKED BY : 李跃刚	DATE : 20131021	PRO.(S) :
APPROVED BY : 彭小宁	DATE :	SHEET :

**WAYING (HONGKONG) SHARES LIMITED**