



1	A0	"H": Data ; "I": Instruction
2	/WR	Write signal
3	DB0	DATA BUS 0
4	DB1	DATA BUS 1
5	DB2	DATA BUS 2
6	DB3	DATA BUS 3
7	DB4	DATA BUS 4
8	DB5	DATA BUS 5
9	DB6	DATA BUS 6
10	DB7	DATA BUS 7
11	/rd	Read signal
12	/RES	Reset signal
13	/CS	Chip select
14	VDD	Power supply (+3.3V)
15	VSS	Power ground
16	A	Backlight (+) +3.3V
17	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: FSTN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -10°C~+60°C
5. STORAGE TEMPERATURE: -20°C~+70°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/160DUTY, 1/12BIAS
8. CONTROLLER: ST7529
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

WAYING (HONGKONG) SHARES LIMITED	
DESIGN:	MODEL NUMBER: WYM240160B
CHECK:	UNITS: MM
APPROVE:	VERSION: A
Unspecified tolerances are ±0.3	
DATE: 2007-04-16	SHEET: 1 OF 1