



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	VO	Contrast adjust
4	RS	Register select
5	R/W	H: Read; L: Write
6	E	Enable signal
7	DB0	DATA BUS 0
8	DB1	DATA BUS 1
9	DB2	DATA BUS 2
10	DB3	DATA BUS 3
11	DB4	DATA BUS 4
12	DB5	DATA BUS 5
13	DB6	DATA BUS 6
14	DB7	DATA BUS 7
15	/CS1	Chip select for IC1.L active
16	RES	Reset signal
17	/CS2	Chip select for IC2.L active
18	/CS3	Chip select for IC3.L active
19	VEE	Negative power output
20	A	Backlight (+) +5V

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: SBNO064 OR EQUIVALENT
9. BACKLIGHT TYPE: YELLOW-GREEN, SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

		DESIGN:	MODEL NUMBER:	UNITS:	MM	
		CHECK:	WYM19264A	VERSION:	A	
APPROVE:		SHEET:	1 OF 1			
Unspecified tolerances are ±0.3					DATE:	2006-04-15