



1	CS1	"CS1CS2"; "L": left screen;
2	CS2	"LH": middle screen; "HL": right screen.
3	VSS	Power ground
4	VDD	Power supply (+5V)
5	VO	Contrast adjust
6	RS	Register select
7	R/W	H: Read; L: Write
8	E	Enable signal
9	DB0	DATA BUS 0
10	DB1	DATA BUS 1
11	DB2	DATA BUS 2
12	DB3	DATA BUS 3
13	DB4	DATA BUS 4
14	DB5	DATA BUS 5
15	DB6	DATA BUS 6
16	DB7	DATA BUS 7
17	A	Backlight (+) +5V
18	K	Backlight (-)
19	VEE	Negative power output
20	/RES	Reset signal

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: SBNO064 OR EQUIVALENT
9. BACKLIGHT TYPE: YELLOW-GREEN, SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WYING WAYING (HONGKONG) SHARES LIMITED

DESIGN:	MODEL NUMBER:	UNITS:	MM
CHECK:	WYM19264B	VERSION:	A
APPROVE:		SHEET:	1 OF 1
Unspecified tolerances are ±0.3			DATE: 2006-08-10